



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Duragard® -35F Ultimate Windshield Wash

Product Use: All proper and legal purposes

Product Number(s): DUR-35WW

Synonyms: Duragard® -35F Window Wash, Duragard® Window Wash, Duragard® Ultimate Window Wash

Company Identification

Advantage Dist. & Lubricants, LLC

3434 Marion RD SE

Rochester, MN 55904

United States of America www.advantagelubes.com

Transportation Emergency Response

CHEMTREC: (800) 424-9300 US, Canada, or U.S. Virgin Islands or (703) 527-3887 all other areas.

Health Emergency

Poison Control Center: Located in the USA. 1-800-222-1222

Product Information

email: info@advantagelubes.com

Product Information: (800) 420-1414, (507) 289-5555 local

SDS Requests: (800) 420-1414, (507) 289-5555 local

SECTION 2: Hazards identification

Classification of the substance or mixture

Flammable Liquids	Category 3
Skin corrosion/irritation	Category 5
Inhalation toxicity	Category 5
Oral toxicity	Category 5
Specific target organ toxicity, single exposure	Category 1

Environmental hazards

Not classified.

OSHA defined hazards

The material is considered hazardous by the OSHA Hazard Communication Standard (29

CFR 1910.1200).

Label elements GHS Hazard

Symbols



Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor. May be harmful if swallowed. May be harmful if inhaled. May cause skin irritation, Causes damage to organs: liver, kidneys, central nervous system and optic nerve.

Precautionary Statements

Prevention

Do not breathe mist. Wear protective gloves/protective clothing/ eye protection/face protection. Take off contaminated clothing and wash before use. Store away from heat and ignition sources. Keep away from oxidizing materials and strong acids.

Response

If on skin (or hair): Wash with soap and water. Get medical attention if irritation develops. Cold water may be used.

If swallowed: Do NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

If in eyes: Check for and remove contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. Cold water may be used. Get medical attention immediately.

If exposed or concerned, immediately call a poison center/doctor.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified (HNOC)

Product is stable.

SECTION 3: Composition/information on ingredients

Substance/mixture: Mixture

Chemical name: N/A

Other means of identification: No

CAS number/other identifiers

Chemical Name	%	CAS #	GHS Classification
METHANOL	32-35	67-56-1	
ETHYLENE GLYCOL	<3	107-21-1	

SECTION 4: First aid measures

Description of first aid measures

Inhalation

Bring accident victims out into the fresh air. Call a physician immediately in severe cases or if recovery is not rapid.

Eyes

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. Cold water may be used. Get medical attention immediately.

Skin Contact

After contact with skin, wash immediately with plenty of water. Remove contaminated clothing and wash before reuse.

Ingestion

DO NOT DELAY. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If victim is alert, rinse mouth and drink 1/2 to 1 glass of water to help dilute the material. Transport to nearest medical facility for additional treatment. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms and effects, both acute and delayed

Potential acute health effects. **Eye contact:** Splashes may cause irritation, pain, eye damage. **Inhalation:** Vapor inhalation is generally not a problem unless heated or misted. Exposure to vapors over an extended time period has caused throat irritation and headache. May cause nausea, vomiting, dizziness and drowsiness. Pulmonary edema and central nervous system depression may also develop. When heated or misted, has produced rapid, involuntary eye movement and coma. **Skin contact:** Irritation, itching, dermatitis. **Ingestion:** Initial symptoms in massive dosage parallel alcohol intoxication, progressing to CNS depression, vomiting, headache, rapid respiratory and heart rate, lowered blood pressure, stupor, collapse, and unconsciousness with convulsions. Death from respiratory arrest or cardiovascular collapse may follow. Lethal dose in humans: 100 ml (3-4 ounces pure ethylene glycol).

Indication of any immediate medical attention and special treatment needed

Kidney toxicity may be recognized by blood in the urine or increased or decreased urine flow. Other signs and symptoms can include nausea, vomiting, abdominal cramps, and diarrhea, lumbar pain shortly after ingestion, and possibly narcosis and death. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or

blurred vision. Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

Specific treatments IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! May cause significant renal, respiratory, and CNS toxicity. May cause significant acidosis. Call a doctor or poison control center for guidance.

Protection of first-aiders N/A

See toxicological information (Section 11)

SECTION 5: Firefighting measures

Extinguishing media

Suitable and Unsuitable

Extinguishing Media:

SMALL FIRE: Use DRY chemical powder, CO₂ or appropriate foam. LARGE FIRE: Use water spray, fog or foam. Do not use water jet. Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture

Vapors may travel back to ignition source. Closed containers exposed to heat may explode. Hazardous thermal decomposition products/Products of combustion. Products of combustion are carbon oxides (CO, CO₂).

Special protective equipment and precautions for firefighters

Do not release runoff from fire control methods to sewers or waterways.

Firefighting equipment/instructions

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

Methods and materials for containment and cleaning up

Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including: the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

SECTION 7: Handling and storage

Precautions for safe handling

Keep away from heat, sparks, open flames, hot surfaces.
– No smoking.

Keep container tightly closed. Ground or bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting, etc. equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fumes, gas, mist, vapors or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, clothing, and eye and face protection.

Conditions for safe storage, including any

Keep container tightly closed in a cool, well-ventilated place. Keep away from oxidizing materials and strong acids. Store in a well-ventilated area. Keep cool. Keep in an area

incompatibilities suitable for flammable liquids..

SECTION 8: Exposure controls/personal protection

Occupational Exposure Limits

Ingredient name	Exposure limits			
Methanol	<u>ACGIH</u>		<u>OSHA</u>	
	(TWA)	(STEL)	(TWA)	(STEL)
	200 ppm	250 ppm	200 ppm; 260 mg/m ³	N/A
Ethylene Glycol	<u>ACGIH</u>		<u>OSHA</u>	
	(TWA)	(STEL)	(TWA)	(STEL)
	100 ppm	N/A	100 ppm	N/A

Appropriate engineering controls and Environmental exposure controls

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Individual protection measures

Hygiene measures

Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use.

Eye/face protection: Use chemical safety goggles.

Skin protection

Hand protection and Body protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Other skin protection

Wash hands and other exposed areas with mild soap and water before eating or drinking.

Respiratory protection: No respiratory protection required under normal circumstances.

Respirator Type(s) (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half face piece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full face piece particulate respirator (NIOSH type N100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, Glycerin, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full face piece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in Oxygen- deficient atmospheres.

SECTION 9: Physical and chemical properties

Appearance

Physical State	Liquid
Form	Liquid
Color	Purple
Odor	Alcohol
Odor threshold	Not determined
pH	8.0
Specific Gravity	0.949
Melting point/Freezing point	-31°F (-35 °C)

Initial boiling point and boiling range	188.6°F (87 °C) estimated
Flash Point	102.2 °F (39°C)
Evaporation Rate	(BuAc=1): Not Determined
Flammability (solid, gas)	Yes
Upper/lower explosive (flammability) limits	
Explosive limit – lower (%)	6% estimated
Explosive limit – upper (%)	36% estimated (Methanol)
Vapor Pressure	128 hPa at 20°C (Methanol)
Vapor Density (Air=1)	1.11 (Methanol)
Relative Density	Not available
Solubility(ies)	
Solubility (water)	Yes
Partition coefficient (n-octanol/water)	Not Established
Auto-ignition temperature	Not Applicable
Decomposition temperature	Not Established
Viscosity	Not Determined
VOC%	34%

SECTION 10: Stability and reactivity

Reactivity	Stable under recommended storage conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Will not occur
Conditions to avoid	Temperatures above the flash point and avoid excessive head, open flame or other sources of ignition.
Incompatible materials	Strong acids, strong bases, strong oxidizing agents, strong reducing agents, magnesium, water, reactive materials, aluminum
Hazardous decomposition	Will not occur

SECTION 11: Toxicological information

Information on toxicological effects Acute toxicity

Product/ingredient name	Test	Results
Acute toxicity, oral (male rat)	LD50 = 7,300 mg/kg	Acute toxicity, dermal LD50 = 15,800 mg/kg
Acute toxicity, inhalation (rat)		LC50: 87.5 mg/l 6.00 Hours
Acute toxicity, oral (male rat)	LD50 = 4,700 mg/kg	Acute toxicity, dermal LD50 = 10,626 mg/kg
Acute toxicity, inhalation (rat)		No Data Available

Summary Comments:

Sensitization

Product/ingredient name	Test	Results
Methanol		No evidence of sensitization effect
Ethylene Glycol		No evidence of sensitization effect

Summary Comments:

Carcinogenicity

Product/ingredient name	Test	Results
Methanol		No known carcinogenic effects
Ethylene Glycol		No known carcinogenic effects

Summary Comments:

Specific target organ toxicity (single exposure)

Product/ingredient name	Test	Results
Methanol	STOT-one-time exposure-oral	>5,000 mg/kg
	STOT-one-time exposure-dermal	>20,000 mg/kg
	STOT-one-time exposure-inhalation	>20,000 mg/kg
Ethylene Glycol	Ingestion may cause drowsiness and dizziness. Inhalation of vapors or mists may cause irritation to the respiratory system.	

Summary Comments:

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Test	Results
Methanol	RfD-oral 0.5 mg/kg	Daily Exposure
Ethylene Glycol		May cause damage to organs or organ systems through prolonged or repeated exposure. Kidney: can cause kidney damage.

Summary Comments:

Liver damage when RfD oral ingestion is exceeded daily.

Aspiration hazard

Product/ingredient name	Test	Results
Methanol	Human exposure studies	Tolerance at 200 ppm/40 hours
Ethylene Glycol	Ingestion may cause drowsiness and dizziness. Inhalation of vapors or mists may cause irritation to the respiratory system	

Summary Comments:

Information on the likely routes of exposure

Inhalation may blur vision. Ingesting may irritate the gastrointestinal tract.

Potential acute health effects

Eye contact: Irritating to the eyes.

Inhalation: Acute exposure of humans to methanol by inhalation or ingestion may result in visual disturbances, such as blurred or dimness of vision, leading to blindness. Neurological damage, specifically permanent motor dysfunction, may also result.

Skin contact: Contact of skin with methanol can produce mild dermatitis in humans.

Ingestion: Ingestion may cause drowsiness and dizziness.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Eye irritation.

Inhalation: Blurred vision.

Skin contact: Skin irritation.

Ingestion: May irritate the gastrointestinal tract, cause nausea, and vomiting.

Potential chronic health effects (Methanol and Ethylene

Glycol) Carcinogenicity: No known carcinogens.

Mutagenicity: No evidence of mutagenic activity.

Teratogenicity: May damage fertility or the unborn child. **Developmental effects:** No data available.

Fertility effects: No data available.

SECTION 12: Ecological information

Toxicity

Acute Fish toxicity: (Methanol)

LC50 - Oncorhynchus mykiss (rainbow trout) - 19,000 mg/l - 96 h

Acute Fish toxicity: (Ethylene Glycol)

LC50 - Oncorhynchus mykiss (rainbow trout) – 18,500 mg/l - 96 h

Acute toxicity for daphnia: (Methanol)

EC50 - Daphnia magna (Water flea) - 24,500 mg/l - 48 h

Acute toxicity for daphnia: (Ethylene Glycol)

EC50 - Daphnia magna (Water flea) – 74,000 mg/l - 48 h

Acute toxicity for algae: (Methanol)

EC50 - Scenedesmus capricornutum (fresh water algae) - 22,000 mg/l - 96 h

Acute bacterial toxicity: (Methanol and Ethylene Glycol)

No data available.

Ecotoxicology Assessment: (Methanol)

Material is expected to be slightly toxic to aquatic life.

Persistence and degradability

Biodegradability: (Methanol and Ethylene Glycol)

When released into the soil, this material is expected to readily biodegrade. When released into water, this material is expected to readily biodegrade. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals.

Stability in water: (Methanol and Ethylene Glycol)

When released into the soil, methanol is expected to quickly evaporate. When released into the soil, these materials are expected to leach into groundwater. When released into the water, this material is expected to have a half-life between 1 and 10 days.

Photodegradation: (Methanol and Ethylene Glycol)

When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals.

Volatility (Henry's Law constant): (Methanol)

Partition coefficient n-octanol/water (log K_{ow}) = -0.77

Volatility (Henry's Law constant): (Ethylene Glycol)

Partition coefficient n-octanol/water (log K_{ow}) = -1.36

Bioaccumulative potential

Bioaccumulation: (Methanol)

Bioaccumulation Cyprinus carpio (Carp) - 72 d at

20°C Bioconcentration factor (BCF): 1.0

Mobility in soil: (Methanol and Ethylene Glycol) Distribution among environmental compartments:

When released into the soil, methanol is expected to quickly evaporate. When released into the soil, this material is expected to leach into groundwater. Ethylene glycol is water soluble and may spread in water systems.

Other adverse effects:

When released into the water, this material is expected to have a half-life between 1 and 10 days. When released into the air, this material is expected to exist in the aerosol phase with a short half-life. When released into air, this material is expected to have a half-life between 10 and 30 days. When released into the air, this material is expected to be readily removed from the atmosphere by wet deposition.

SECTION 13: Disposal considerations

Disposal instruction Dispose of contents/container in accordance with local/regional/national/international regulations, laws, ordinances and statutes.

SECTION 14: Transport information

DOT

Proper Shipping Name: METHANOL

Transport hazard class(es): 3

Packing Group: III

Land Transport ADR/RID and GGVS/GGVE (Cross Border / Domestic)

Transport Hazard Class(es): N/A

Maritime Transport IMDG/GGVSea

Transport Hazard Class(es): N/A

Marine Pollutant: No

Air Transport ICAO-TI and IATA-

DGR Transport Hazard Class(es):

N/A

SECTION 15: Regulatory information

Chemical Inventory Status-Part 1

Ingredient (CAS#)	TSCA	EC	Japan	Australia
Methanol (67-56-1)	Yes	Yes	Yes	Yes

Chemical Inventory Status-Part 2

Ingredient (CAS#)	Korea	Canada	Canada	Philippines
		DSL	NDSL	
Methanol (67-56-1)	Yes	Yes	No	Yes

Federal, State & International Regulations-Part 1

Ingredient (CAS#)	SARA		SARA	
	RQ	TPQ	List	Category
Methanol (67-56-1)	No	No	Yes	No

Federal, State & International Regulations-Part 2

Ingredient (CAS#)	RCR		TSCA
	CERCL	261.33	8(d)
Methanol (67-56-1)	5000 lb.	U154	No

Chemical Weapons Convention: No

TSCA 12b: No

CDTA: No

SARA
311/312:

Acute: Yes,

Chronic: Yes, Fire: Yes,

Pressure: No,

Reactivity: No Mixture/Liquid

Australian Hazchem Code: 2PE

Poison Schedule: No information found

SECTION 16: Other information

Revision Date 07/21/2016

Supersedes: 04/13/2015

Version # 1a

Disclaimer The information contained herein is believed to be accurate and makes no representation or warranty, express or implied, regarding, and assumes no liability for the accuracy or completeness of the information. The Buyer assumes all responsibility for handling, using and/or reselling the Product in accordance with applicable federal, state, and local law. This SDS shall not in any way limit or preclude the operation and effect of any of the provisions of the terms of conditions of sale.