



DURAGARD® IS A REGISTERED TM OF ADVANTAGE DIST. LLC, ROCH., MN 55904 Product Code: DURINDHZAW100

DURAGARD®

INDUSTRIAL AW-100 HIGH ZINC HYDRAULIC OIL

ADVANCED TECHNOLOGY, PREMIUM LUBRICANTS

DURAGARD® DIAMOND PLATE® Industrial AW-100 High Zinc Hydraulic Oil is a premium quality, HVI-MV Group-II Hydro cracked anti-wear hydraulic oil designed to meet the requirements of fluid power / hydraulic systems. **It is formulated with select 100% HVI-MV Group-II Hydro cracked clear base oils that provide superior low temperature fluidity and high temperature film strength that simply cannot be achieved using conventional mineral base oils.** The formulation uses a proven anti-wear additive system that is effective in reducing wear in pumps.

DURAGARD® DIAMOND PLATE® Industrial AW-100 High Zinc Hydraulic Oil also has excellent water separation, rust and corrosion prevention, oxidation stability, and anti-foam properties. The true multi-viscosity, broad temperature feature allows even and continuous power transmission over a wider temperature range with increased accuracy compared to single weight hydraulic oils.

Customer Benefits with *DURAGARD® DIAMOND PLATE PROTECTION®*

- * Exceptional protection against wear from contaminants and higher operating temperatures and pressures ensures longer equipment life
- * Maintains viscosity, even under higher operating temperatures, and has sufficient reserve of key additives, resulting in longer fluid life and reduced operating costs
- * Reduced foaming ensures smooth, efficient operation and proper lubrication of all parts in the system
- * Formulated to provide 5,000 hours of oxidation stability.

Application Specifications:

DURAGARD® DIAMOND PLATE® Industrial AW-100 High Zinc Hydraulic Oil
This product meets, or exceeds the requirements similar to the following manufacturers and global specifications:

ASTM D6158
Eaton E-FDGN-TB002-E, 35VQ25A
Bosch Rexroth
DIN 51524, Part 1,2,3
General Motors LS-2

JCMAS HK
Parker Denison HF-0, HF-1, HF-2
Racine
Sperry Vickers/Eaton I-286-S, M-2950-S
US Steel 127, 136

Product Containers Available:

Bulk * 55 gal. * 30 gal. * 5 gal. pails * 2.5 gal/2pk * 1 gal/4pk

Typical Physical Specifications:

Product Code: DURINDHZAW100

INSPECTION INFORMATION	TEST METHOD	TYPICAL VALUE
Gravity API	ASTM D287	30.12
Specific Gravity @60°F (15.6°C)	ASTM D4052	0.8755
Viscosity @ 40°C cSt	ASTM D445	99.86
Viscosity @ 100°C cSt	ASTM D445	11.31
Viscosity Index	ASTM D2270	99
Pour Point °C (°F)	ASTM D5950	-30 °C (-22 °F)
Color	ASTM D1500	0.5
Zinc, wt. %	ASTM D5185	0.041
Phosphorus, wt. %	ASTM D5185	0.033
Calcium, wt. %	ASTM D5185	0.003
Sulfur, wt. %	ASTM D4951	0.065
Oxidation Hours	ASTM D943	5000

Typical test data average values only, minor variations which do not affect product performance are to be expected during normal manufacturing.

READ ENTIRE SDS BULLETIN FOR HANDLING AND SAFETY INFORMATION

ADVANTAGE

Advantage Distributing and Lubricants, LLC

3434 Marion Rd SE
Rochester, MN 55904
507-289-5555



http://duragardoil.com/duragard_ind_aw100_high_zinc_hyd_2055_ghs.php