



DURAGARD®

SAE 10WT SINGLE GRADE HEAVY DUTY ENGINE OIL

Premium Hydro-Cracked Lubricants
SEVERE SERVICE LOW ASH ENGINE & TRANSMISSION OILS

Duragard® SAE 10WT Single Grade Heavy Duty Engine & Transmission Oil is specially formulated with a select High Viscosity Index (HVI) Group-II Hydro-cracked base oils combined with potent detergent dispersants, anti-wear additives, anti-oxidants, defoamers, and pour point depressant compounds that provide superior low temperature fluidity and extraordinary high temperature film strength to prevent metal-to-metal contact.

Duragard® SAE 10WT Single Grade Heavy Duty Engine & Transmission Oil meets the performance requirements of typical of API CF and can be used in applications where a 10WT Single Grade API CF fluid is specified. Recommended for older diesel engines.

Customer Benefits:

- * Meets API CF
- * Reduces deposits of sludge, varnish and carbon on engine parts.
- * Superior low temperature fluidity.
- * Provides excellent high film strength properties under high temperatures.
- * Outstanding oil performance under harsher conditions.
- * Suitable for heavy equipment used for construction, mining or quarry operations, and farming.



Product Code: DUR10

Product Containers Available:



www.duragardoil.com

Made in USA with domestic and imported products.

2020 © Copyright ADVANTAGE DIST., LLC All Rights Reserved

Diamond Plate Protection®

DURAGARD® IS A REGISTERED TM OF ADVANTAGE DIST. LLC, ROCH., MN 55904

Rev 09/2020 PG-1



DURAGARD® SAE 10WT SINGLE GRADE HEAVY DUTY ENGINE OIL

Typical Physical Specifications:

SAE 10WT

Product Code: DUR10

INSPECTION INFORMATION	TEST METHOD	TYPICAL VALUE
Cold Cranking Simulator at (°C), cP	ASTM D5293	4025 (-25)
Color	ASTM D1500	2.5
Flash Point °C	ASTM D92	206
Flash Point °F	ASTM D92	403
Gravity, °API	ASTM D287	31.42
Pour Point °C (°F)	ASTM D5950	-36°C (-33°F)
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8685
Viscosity @ 100°C cSt	ASTM D445	6.794
Viscosity @ 40°C cSt	ASTM D445	42.83
Viscosity Index	ASTM D2270	114
Zinc, wt. %	ASTM D5185	0.086

Typical test data average values only, minor variations which do not affect product performance are to be expected during normal manufacturing.

READ ENTIRE SDS BULLETIN FOR HANDLING AND SAFETY INFORMATION

#1 In Customer Service And Technical Support

ADVANTAGE

Advantage Distributing and Lubricants, LLC

3434 Marion Rd SE

Rochester, MN 55904

1-800-420-1414

507-289-5555

INFO@ADVANTAGELUBES.COM